



Mounting instructions for Big Daddy Fishing Rod Racks

Phillips screwdriver is required and not included.

1. Layout all parts and components on a flat surface.
2. Determine a location for the rack, either overhead on a ceiling, or on a wall. If you're mounting on a wall, you may choose to do so horizontally or vertically. If desired, use a level to make sure the rod rack is aligned to your liking.
3. Hold one rack in the desired location and mark the location for the wall anchors using the 6 holes in the base of the rack as a template.
4. Using an awl or drill, create holes on each marking. Make sure the diameter and depth of each hole is the same as the wall anchors.
5. Insert wall anchors into each hole.
6. Holding the rod rack against the surface you are mounting on, drive the screws through the holes in the base of the rod rack and into the wall anchors.
7. To position your second rod rack, you may insert one of your fishing poles into the newly installed rod rack, and use the opposite end of the pole as a reference point.
8. Repeat steps 3-6 to install your second rod rack.
9. With additional rod rack units, you can expand the capacity of the first unit, from either end, by joining the interlocking heads and tails of the racks.

Package Contents

| | |
|-------|----------------|
| 2pcs | Rod Racks |
| 12pcs | ┆ Screws |
| 12pcs | ┆ Wall Anchors |

Tools needed for install (not supplied)

- Phillips screwdriver
- Awl or drill
- Level (optional)

